

### Notes on Installation and usage

1. Users should not disassemble the camera from the front direction.
2. Always handle the camera with care. Please do not apply a shock or vibration as much as possible and take cautions not to cause damage or make a scratch on the camera due to careless storage.
3. Please do not install the camera with the rainy place or highly humid areas. And do not operate the camera in the wet place.
4. Do not clean the camera body with the strong abrasives or soaps. When the camera becomes dirty clean it with the dry rags. Especially make sure to use the dedicated rags for lens to clean the dome cover.
5. Please select the camera in the cool area that is not exposed to the direct sunlight. If you do it can cause bad effects on the product.

### Specifications

MODEL:	CCD-2	CMOS-2
Image Sensor:	1/3" Sharp CCD	CMOS
System:	NTSC	
Resolution:	460TV lines	380TV lines
Number of Pixels:	NTSC: 510(H) × 492(V)	NTSC: 510(H) × 492(V)
Scanning system:	NTSC: 525 Lines, 60 Field/sec	
Minimum illumination:	0.1 LUX at F 1.4	
Synchronizing system:	Internal	
Scanning system:	2:1 Interlaced	
Video output:	1Vp-p 75 ohm composite	
S/N Ratio:	Min 52 dB	
Power:	DC 12V ± 1V	
Operating environment:	0°C - +50°C	
Lens:	3.5, 6, 8mm, pin hole at option	

## CCD/CMOS CAMERA

## User's Manual

