

EGC-4 EGC-5 EGC-6


COMPONENT SPEAKER SYSTEM INSTALLATION MANUAL

Thank you for purchasing the Soundstream Edge series component speaker system. This state of the art system has been engineered with the media in mind. The engineers at Soundstream highly recommend an authorized dealer to install a component system for optimal performance and an extended warranty period. If you choose to install this product yourself, please read the installation manual thoroughly before starting.

Caution
• Before cutting any holes, make sure that there is proper clearance for the installation. Do not cut and wiring is clear of objects that may impede the proper installation.
• Keep speaker magnets away from computer systems that are mounted on edges and moving parts.


• To prevent short-circuits and product damage, keep all wiring away from sharp edges and moving parts.

Note
After you have completed the installation process, there is some final adjustment to be made. Please refer to the "Adjustment" section of the manual for more information. Please adjust the shoring pin configuration to the desired tweeter level that is required.




INSTALLATION OF TWEETER

Surface Mount




Flush Mount




1. Choose a proper installation point for the tweeter. The tweeter should be mounted in a location that is not near any other wires and get protected from moisture. The tweeter should be mounted in a location that is not near any other wires and get protected from moisture.
2. Remove the tweeter and get the shoring pin to the wall. Place the tweeter and the tweeter magnet on the wall.

1. Choose a proper installation point for the tweeter.
 2. The tweeter should be mounted in a location that is not near any other wires and get protected from moisture. The tweeter should be mounted in a location that is not near any other wires and get protected from moisture.
 3. Before cutting the holes be sure that you have a proper installation point for the tweeter.
 4. Housing depth.
- WIRING BEFORE INSTALLING THE TWEETER**
WIRING BEFORE INSTALLING THE TWEETER

WIRING INSTRUCTIONS



WOOFER INSTRUCTION (EGC-4/EGC-5/EGC-6)



1. Using mounting templates for the speaker, mark the correct mounting location with a pencil or pen.
2. Cut out the panel at the marking and drill 4 holes for the mounting bolts to pass through.
3. Separate the grill mesh from the grill frame.
4. Connect the wires coming from the crossover to the speaker. Be sure to match the polarity correctly.
5. Insert grill frame & speaker into the speaker mounting hole at the rear panel and attach the speaker with bolts & nuts provided.
6. Put the grill mesh back with the grill frame.

TEMPLATE (EGC-4/EGC-5/EGC-6)

