Notes on Installation and usage

- 1. Users should not disassemble the camera from the front direction.
- 2. Always handle the camera with care. Please do not apply a shock or vibration as much aspossible and take cautions not to cause damage or make a scratch on the camera due tocareless storage.
- Please do not install the camera with the rainy place or highly humid areas. And do not
 operate the camera in the wet place.
- 4. Do not clean the camera body with the strong abrasives or soaps. When the camera becomes dirty, clean it with the dry rugs Especially make sure to use the dedicated rugsfor lens to clean the dome cover.
- Please select the camera in the cool area that is not exposed to the direct sunilight. If youdo it can cause bad effects on the product.

Specifications

MODEL:	CCD-1	CMOS-1
Image Sensor:	1/3 " Sharp CCD	CMOS
System:	NTSC	
Resolution:	420TV lines	380TV lines
Number or Pixels:	NTSC:512(H) × 582(V)	NTSC: 510(H)X492(V)
White balance:	Auto 2800k-8200k	
Minimum illumination:	0.1 LUX at F 1.4	
Synchronizing system:	Internal	
Scanning system:	2:1 Interlaced	
Video output:	1∨p-p 75 ohm composite	
S/N Ratio:	More than 50 dB	
Power:	DC12V(Talerence:9v-15v)	
Infrared Wavelength:	8-10M	
Lens mount Standard	f=3.6(92°),f=3.7(90°)	
Electronic iris(Auto):	1/50,1/60-1/100.000sec.	
Gamma correction:	0.45	

CCD/CMOS CAMERA

User's Manual



