

Notes on Installation and usage

1. Users should not disassemble the camera from the front direction.
2. Always handle the camera with care. Please do not apply a shock or vibration as much as possible and take cautions not to cause damage or make a scratch on the camera due to careless storage.
3. Please do not install the camera with the rainy place or highly humid areas. And do not operate the camera in the wet place.
4. Do not clean the camera body with the strong abrasives or soaps. When the camera becomes dirty clean it with the dry rags. Especially make sure to use the dedicated rags for lens to clean the dome cover.
5. Please select the camera in the cool area that is not exposed to the direct sunlight. If you do it can cause bad effects on the product.

Specifications

| | | |
|------------------------|--|---------------------|
| MODEL: | CCD-3 | CMOS-3 |
| Image Sensor: | 1/4 " Sharp CCD | CMOS |
| System: | NTSC | |
| Resolution: | 420TV lines | 380TV lines |
| Number of Pixels: | NTSC:510(H)× 492(V) | NTSC: 510(H)X492(V) |
| White balance: | 850nm Auto tracking white balance | |
| Minimum illumination: | 1Lux(F:2.0),0 lux with built-in IR LED | |
| Synchronizing system: | Internal Synchronization | |
| Gamma Characteristic: | 0.45 | |
| Video output: | 1Vp-p 75 ohm composite | |
| S/N Ratio: | ≥48dB(AGC Off) | |
| Power Supply: | DC12V±10% 400mA | |
| Infrared Wavelength: | 10M | |
| Lens:Board Lens: | 3.6mm/F2.0(optional) | |
| Electronic iris(Auto): | 1/50,1/60-1/100.000sec. | |
| Infrared Lamps: | NIGHT/DAY | |

CCD/CMOS CAMERA

User's Manual

